



EITA-Schneider®

Commercial Lift (Machine Room Less) Standard Duty Table

Capacity		Speed (m/s)	Lift Car Internal a x b (mm)	Car Height (mm)	Shaft Size X x Y	Overhead (mm)	Pit Depth (mm)	Travel	Entrance Opening (mm)	Structure Door Opening (mm)		Type of Entrance
Persons	kg									Wide Jamb	Narrow Jamb	
6	410	1	1000 x 1150	2500	1870 x 1850	4400	1700	≤15	800 x 2100	1100 x 2250	1000 x 2250	2-Panel Center Opening
		1.5				4550	1800	>15, ≤30				
		1.75				4650	1900	>30, ≤45				
8	545	1	1100 x 1300	2500	1950 x 1920	4400	1700	≤15	800 x 2100	1100 x 2250	1000 x 2250	2-Panel Center Opening
		1.5				4550	1800	>15, ≤30				
		1.75				4650	1900	>30, ≤45				
9	615	1	1200 x 1300	2500	2000 x 1920	4400	1700	≤15	800 x 2100	1100 x 2250	1000 x 2250	2-Panel Center Opening
		1.5				4550	1800	>15, ≤30				
		1.75				4650	1900	>30, ≤45				
10	680	1	1250 x 1400	2500	2040 x 1970	4400	1700	≤15	800 x 2100	1100 x 2250	1000 x 2250	2-Panel Center Opening
		1.5				4550	1800	>15, ≤30				
		1.75				4650	1900	>30, ≤45				
11	750	1	1300 x 1450	2500	2060 x 2000	4400	1700	≤15	800 x 2100	1100 x 2250	1000 x 2250	2-Panel Center Opening
		1.5				4550	1800	>15, ≤30				
		1.75				4650	1900	>30, ≤45				
13	885	1	1350 x 1600	2500	2200 x 2070	4400	1700	≤15	900 x 2100	1200 x 2250	1100 x 2250	2-Panel Center Opening
		1.5				4550	1800	>15, ≤30				
		1.75				4650	1900	>30, ≤45				
15	1025	1	1550 x 1600	2500	2310 x 2070	4400	1700	≤15	900 x 2100	1200 x 2250	1100 x 2250	2-Panel Center Opening
		1.5				4550	1800	>15, ≤30				
		1.75				4650	1900	>30, ≤45				
		2				4750	1900	>45, ≤60				
	1	1200 x 2100	1	2500	2200 x 2500	4400	1700	≤15	900 x 2100	1200 x 2250	1100 x 2250	2-Panel Center Opening
			1.5			4550	1800	>15, ≤30				
			1.75			4650	1900	>30, ≤45				
			2			4750	1900	>45, ≤60				
17	1160	1	1800 x 1500	2500	2850 x 2150	4450	1750	≤15	1000 x 2100	1300 x 2250	1200 x 2250	2-Panel Center Opening
		1.5				4600	1850	>15, ≤30				
		1.75				4750	1950	>30, ≤45				
		2				4750	1950	>45, ≤60				
	1	1300 x 2100	1	2500	2450 x 2500	4450	1750	≤15	1000 x 2100	1300 x 2250	1200 x 2250	2-Panel Center Opening
			1.5			4600	1850	>15, ≤30				
			1.75			4750	1950	>30, ≤45				
			2			4750	1950	>45, ≤60				

Commercial Lift (Machine Room Less) Standard Duty Table

Capacity		Speed (m/s)	Lift Car Internal a x b (mm)	Car Height (mm)	Shaft Size X x Y	Overhead (mm)	Pit Depth (mm)	Travel	Entrance Opening (mm)	Structure Door Opening (mm)		Type of Entrance
Persons	kg									Wide Jamb	Narrow Jamb	
20	1365	1	1950 x 1600	2500	3050 x 2200	4450	1750	≤15	1100 x 2100	1400 x 2250	1300 x 2250	2-Panel Center Opening
		1.5				4600	1850	>15, ≤30				
		1.75				4750	1950	>30, ≤45				
		2				4750	1950	>45, ≤60				
		1	1400 x 2250	2500	2550 x 2650	4450	1750	≤15				
		1.5				4600	1850	>15, ≤30				
		1.75				4750	1950	>30, ≤45				
		2				4750	1950	>45, ≤60				
21	1430	1	1800 x 1800	2500	2900 x 2350	4450	1750	≤15	1100 x 2100	1400 x 2250	1300 x 2250	2-Panel Center Opening
		1.5				4600	1850	>15, ≤30				
		1.75				4750	1950	>30, ≤45				
		2				4750	1950	>45, ≤60				
		1	1400 x 2300	2500	2550 x 2700	4450	1750	≤15				
		1.5				4600	1850	>15, ≤30				
		1.75				4750	1950	>30, ≤45				
		2				4750	1950	>45, ≤60				
24	1635	1	2100 x 1700	2500	3200 x 2300	4450	1750	≤15	1100 x 2100	1400 x 2250	1300 x 2250	2-Panel Center Opening
		1.5				4600	1850	>15, ≤30				
		1.75				4750	1950	>30, ≤45				
		2				4750	1950	>45, ≤60				
		1	1500 x 2400	2500	2600 x 2800	4450	1750	≤15				
		1.5				4600	1850	>15, ≤30				
		1.75				4750	1950	>30, ≤45				
		2				4750	1950	>45, ≤60				

Note/Remarks:

- (a) All dimensions are for reference only and subject to changes without prior notice.
- (b) For construction purpose, kindly refer to the approved shop drawing for the respective project.
- (c) For requirements beyond the above standard specifications, kindly consult our sales personnel.