



MODEL	FGL30-800 (4800 PEOPLE/HOUR)					FGL30-1000 (6000 PEOPLE/HOUR)					SHIPPING DIMENSION		STRUCTURE OPENING SINGLE DRIVING	STRUCTURE OPENING DOUBLE DRIVING
	NET WEIGHT (kN)	SUPPORTING LOAD (kN)			MOTOR POWER (kW)	NET WEIGHT (kN)	SUPPORTING LOAD (kN)			h	T			
		R1	R2	R3			R1	R2	R3					
6000	75	45	37	93	11	107	51	43	107	15	3290	17760	16057	
6500	83	47	39	98	11	111	53	45	113	15	3300	18750	16923	
7000	87	49	41	103	11	116	56	48	119	15	3320	19700	17789	
7500	92	51	43	108	15	120	58	50	124	15	3330	20750	18655	
8000	97	53	45	113	15	125	60	52	130	18.5	3340	21740	19521	
8500	103	55	47	118	15	129	62	54	135	18.5	3350	22740	20387	
9000	110	57	49	123	15	134	69	58	144	11 x 2	3510	24110		21670
9500	123	59	51	128	15	139	71	60	149	11 x 2	3530	25110		22536
10000	129	61	53	133	18.5	143	73	62	154	11 x 2	3540	26100		23402

MODEL	A	B	C	D	E
FGL30-800	800	1038	1340	1400	16900
FGL30-1000	1000	1238	1540	1600	15700

NOTE: E DENOTES THE MAXIMUM DISTANCE BETWEEN TWO SUPPORTING POINTS