



MODEL	FPL35-600 (3600 PEOPLE/HOUR)					FPL35-800 (4800 PEOPLE/HOUR)					FPL35-1000 (6000 PEOPLE/HOUR)					STRUCTURE OPENING (L) ±10		SHIPPING DIMENSION	
	TRAVELLING WEIGHT (mm)	NET WEIGHT (kN)	SUPPORTING LOAD (kN)	MOTOR POWER (kW)	STRUCTURE OPENING (L) ±10	NET WEIGHT (kN)	SUPPORTING LOAD (kN)	MOTOR POWER (kW)	STRUCTURE OPENING (L) ±10	NET WEIGHT (kN)	SUPPORTING LOAD (kN)	MOTOR POWER (kW)	STRUCTURE OPENING (L) ±10	NET WEIGHT (kN)	SUPPORTING LOAD (kN)	MOTOR POWER (kW)	h	T	
3000	54	43	39	5.5	9526	56	49	44	5.5	60	56	50	5.5	9109	2850	10180			
3500	57	46	41	5.5	10241	60	52	47	5.5	64	60	53	5.5	9824	2890	11030			
4000	60	49	44	5.5	10955	63	56	50	5.5	67	64	57	7.5	10538	2920	11890			
4500	64	52	46	5.5	11669	66	59	53	7.5	71	67	60	7.5	11252	2940	12750			
5000	67	54	49	5.5	12383	70	62	56	7.5	74	71	64	11	11966	2970	13610			
5500	70	57	51	7.5	13097	73	65	59	8	82	77	69	11	12680	2980	14470			
6000	73	60	54	7.5	13811	76	69	61	11	85	81	72	11	13394	3000	15330			

MODEL	A	B	C	D	E
FPL35-600	600	838	1140	1200	18500
FPL35-800	800	1038	1340	1400	16900
FPL35-1000	1000	1238	1540	1600	15700

NOTE: WHEN STRUCTURE OPENING (L) IS LONGER THEN (E) AN INTERMEDIATE SUPPORT SHALL BE ADDED AT MIDDLE